







# City Ranger 2250 Snow V-Blade

When heavy and icy snow covers the ground, you need the snow v-blade close at hand. It uses the tip of the 'V' to cut through heavy and encrusted snow, separating and pushing it to both sides. Even large amounts of snow are removed with ease.

The v-blade can also be configured as a 'Y' to allow snow to be transported away — very useful in car parks, markets, enclosed courtyards and other locations where snow needs to be gathered in one place.

## Soft ground? No problem

The snow v-blade always follows the terrain, whether soft, hard or uneven. The ability to distribute weight to the basic machine even allows the snow v-blade to clear gravel paths, as the reduced weight prevents it from digging into the gravel. The snow v-blade height can also be adjusted to cater for uneven pavements and low curbs.

#### **Dual efficiency**

The combination of the quick-working snow v-blade at the front and the salt and sand spreader at the back of the basic machine means that snow clearing and salting are completed in a single pass — on snow up to 50 cm thick and 1.2—1.4 metres wide.

As well as being extremely efficient, the snow v-blade is also very quiet and comfortable to operate.



When you change attachments, the City Ranger 2250 hydraulic hoses are connected at the turn of a handle!











1,400 mm

### **Special features**

Handles snow up to 50 cm thick
Clearing width 1.2—1.4 m
Both blades hydraulically-adjusted
A-frame featuring integrated vibration damping — Quiet and comfortable
Steel blades as standard
Safety tilt system
Well suited to gravel paths due to weight distribution to basic machine
2 skids for height adjustment - uneven pavements and low curbs require e.g. high adjustment
Lateral floating position — skid and blade follow the terrain

#### Extra equipment

Rubber scraping edge for surfaces that require extra care

Often used in combination with the Salt and Sand Spreader

#### **Dimensions**

Fitted:

 Length
 3,000 mm

 Width
 1,400 mm

 Height
 1,960 mm

**Storage dimensions:** 

Length500 mmWidth1,400 mmHeight600 mm

Technical data:

Weight 118 kg Clearing width 1,200–1,400 mm

**Ground clearance** 

under scraper 240 mm

**Ground clearance** 

under support strut 215 mm

## **CE** certified according to EU Directive

**Your Nilfisk Outdoor Dealer** 

